

### PRODUCT DESCRIPTION

SHERA plank is a unique fibre cement composite of natural fibres bonded tightly in a high-grade silicate structure. This autoclaved wood-grain siding acquires impressive toughness, yet remains flexible and dimensionally stable. It is a cellulose cement plank that contains absolutely no asbestos fibre, no fibre glass fibres or formaldehyde.

### TECHNICAL DATA

- DENSITY: 1300 - 1350 kg/m<sup>3</sup>
- THICKNESS TOLERANCE: + 10%
- WATER ABSORPTION: <35%
- MOISTURE CONTENT: <15%
- PH VALUE: 7
- FIRE RESISTANCE: CLASS 1

### DIMENSIONS

Thickness	8mm
Width	200mm
Length	4000mm
Weight	9.6kg/pcs
Profile	Teak
Finish	Undecorated



### ADVANTAGES

- Weather resistant
- Immune to water damage
- Fire resistant
- Provides sound insulation
- Shatter resistant
- Low shrinkage
- Flexible
- High degree of workability
- Termite resistant



Weather Resistance



Fire Resistance



Immune to Water Damage



Sound Insulation



High Workability



Low Shrinkage



Termite Resistance



Non-Asbestos

**KZN HEAD OFFICE:**  
2 Corobrik Place, Riverhorse  
Valley Business Estate, Durban.  
Tel: 031 569 6090

**BALLITO:**  
2 Apex Drive,  
North Point, Ballito.  
Tel: 032 946 0422

**GAUTENG:**  
21 Flower Close,  
Tunney, Germiston.  
Tel: 011 822 8142

**WESTERN CAPE:**  
Unit 6 Oude Molen Park,  
7 Oude Molen Road,  
Ndabeni, Cape Town  
Tel: 021 002 7038